

Product sheet Royal


Side-hung Windows

LIF1283, Inward Opening Window Triple Glazing

Frame thickness:	128 mm
Sound reduction:	34 - 45 dB
U-value:	1,0 - 1,3 W/m ² K


Product images

Original configuration



LIF1283

LIF1283 Royal inward opening window triple glazing



LIF1283

LIF1283 Royal inward opening window triple glazing



LIF1283

LIF1283 Royal inward opening window triple glazing




LIF1283

Product sheet Royal

Side-hung Windows


LIF1283, Inward Opening Window Triple Glazing



Window sill

Window sill has to be located in the furthest channel.

Alternative profiles



LIF1283

LIF1283 Royal inward opening window triple glazing. Visible weep holes



LIF1283

LIF1283 Royal inward opening window triple glazing. Visible weep holes

Multi-light windows and accessories



LIF1283

LIF1283 Two light window



LIF1283

LIF1283 Two light window

MAIN OFFICE

Fagersjögatan 3, S-598 97 Mariannelund

Phone +46 496-707 00

Fax +46 496-211 60

E-mail address: info@leiab.se

Page 2 of 4

Product sheet Royal

Side-hung Windows

LIF1283, Inward Opening Window Triple Glazing




LIF1283
LIF1283 Three light window



LIF1283
LIF1283 Three light window

Royal function and design



LIF1283



LIF1283

References



Project name Brf Ingegerd

MAIN OFFICE
Fagersjögatan 3, S-598 97 Mariannelund
Phone +46 496-707 00
Fax +46 496-211 60
E-mail address: info@leiab.se

Page 3 of 4

Product sheet Royal

Side-hung Windows

LIF1283, Inward Opening Window Triple Glazing

Client Valbo Fönsterteknik AB
Location/town Uppsala
Window model Royal