

Product sheet Stil


Fixed Lights

LFI953, Fixed Light Triple Glazing, Internally Glazed

Frame thickness:	95 mm
Sound reduction:	32 - 46 dB
U-value:	1,0 - 1,3 W/m ² K


Product images

Original configuration



LFI953

LFI953 Stil fixed light triple glazing. Internally glazed



LFI953

LFI953 Stil fixed light triple glazing. Internally glazed



LFI953

LFI953 Stil fixed light triple glazing. Internally glazed




LFI953

Product sheet Stil

Fixed Lights

LF1953, Fixed Light Triple Glazing, Internally Glazed



Window sill

Window sill has to be located in the furthest channel.

Alternative profiles



LF1953 Stil fixed light triple glazing. Internally glazed. Visible weep holes



LF1953

LF1953 Stil fixed light triple glazing. Internally glazed. Visible weep holes

References



Project name Nyponlunden
Client Peab Sverige AB
Location/town Örebro
Window model Stil



Project name Smedbyns Förskola
Client Byggkompaniet i Nässjö AB
Location/town Huskvarna
Window model Stil

Product sheet Stil

Fixed Lights

LFI953, Fixed Light Triple Glazing, Internally Glazed



Project name	Studentcity
Client	Peab Sverige AB
Location/town	Örebro
Window model	Stil