

Product sheet Haga


Fixed Lights

LFI1003, Fixed Light Triple Glazing, Internally Glazed


Frame thickness:	100 mm
Sound reduction:	32 - 46 dB
U-value:	1,0 - 1,3 W/m ² K

Product images

Original configuration



LFI1003
LFI1003 Haga inward opening window triple glazing



LFI1003
LFI1003 Haga inward opening window triple glazing



LFI1003
LFI1003 Haga inward opening window triple glazing




LFI1003

Product sheet Haga

Fixed Lights

LFI1003, Fixed Light Triple Glazing, Internally Glazed



Window sill

Window sill has to be located in the furthest channel.

Alternative profiles



LFI1003

LFI1003 Haga inward opening window triple glazing. Visible weep holes



LFI1003

LFI1003 Haga inward opening window triple glazing. Visible weep holes

References



Project name BB Sophiahemmet Hus 30
Client Ebab i Stockholm AB
Location/town Stockholm
Window model Haga



Project name Brf Strandkanalen
Client Peab Sverige AB
Location/town Gävle
Window model Haga

Product sheet Haga

Fixed Lights

LFI1003, Fixed Light Triple Glazing, Internally Glazed



Project name Brf. Orangeriet
Client Tornstaden
Location/town Stockholm
Window model Haga



Project name KV. Gubben 8
Client HSB Östra
Location/town Norrköping
Window model Haga



Project name Kv. Mjölaren
Client Tegelstaden Bygg AB
Location/town Norrköping
Window model Haga



Project name KV. Våghalsen 6
Client Tegelstaden Bygg AB
Location/town Eskilstuna
Window model Haga