

Product sheet Haga

Fixed Lights

LFU1003, Fixed Light Triple Glazing

Frame thickness:	100 mm
Sound reduction:	32 - 46 dB
U-value:	0,9 - 1,3 W/m ² K


Product images

Original configuration



LFU1003

LFU1003 inward opening window triple glazing. Visible weep holes



LFU1003

LFU1003 Haga inward opening window triple glazing



LFU1003

LFU1003 Haga inward opening window triple glazing



LFU1003

Product sheet Haga

Fixed Lights


LFU1003, Fixed Light Triple Glazing



Window sill

Window sill has to be located in the furthest channel.

Multi-light windows and accessories



Product sheet Haga

Fixed Lights

LFU1003, Fixed Light Triple Glazing



LFU1003

LFU1003 Haga inward opening window triple glazing.




LFU1003

LFU1003 Haga inward opening window triple glazing.

References



Project name BB Sophiahemmet Hus 30
Client Ebab i Stockholm AB
Location/town Stockholm
Window model Haga



Project name Brf. Sandåkern - HSB
Client Peab Sverige AB
Location/town Umeå
Window model Haga



Project name BRF. Söderport
Client XL-Bygg Norrby Trä
Location/town Borås



Project name Kaffestugan
Client Ikano Bostad
Location/town Sundbyberg

Product sheet Haga

Fixed Lights

LFU1003, Fixed Light Triple Glazing

Window model Haga



Project name KV Örbyhus - Teatergatan
Client Kungälv's Trävaru AB
Location/town Göteborg
Window model Haga

Window model Haga



Project name KV. Gubben 8
Client HSB Östra
Location/town Norrköping
Window model Haga



Project name Kv. Nålskäran
Client Peab Sverige AB
Location/town Göteborg
Window model Haga



Project name Porslinsfabriken 2C
Client Peab Sverige AB
Location/town Göteborg
Window model Haga



Project name Rosen 7
Client Peab Sverige AB
Location/town Umeå
Window model Haga